

GENERAL CAR INFO		DIMENSIONS/CAPACITIES		SPECIALTY SUPPLIERS AND PART NUMBERS			RS
Built date	1955	Length (strikers)		Truck type	S-2-A	Draft Gear	AAR SPEC. 901
Car builder	CB&Q	Coupled length		Bols. Patt./ AAR Code	NA	Cushioning	NA
AFE number		Truck ctrs.		Side Frame/AAR Code		Brake system	Body mounted
AAR Mech. Des.		Length over end sills	60'-0"	Truck spring group		Control valve	AB
AAR Car Code		Width over side sills	9'-6"	Snubbing type		Brake cylinder	10"x12"
GST Code	NA	Extreme width	10'-6"	Snub. sprg. group	NA	Slack adjuster	NA
Clearance plate		Extreme height		Column wear plate		Brake beam	NO. 18
C.G Empty		Gross rail load		Pedestal roof liners		Brake beam wear elim.	NA
C.G Loaded		Lightweight	65,000 lbs.			Brake shoes	NA
Min. curve-Coupled		Load limit @ 220K		Roller bearing		Handbrake	Drop mast
Min. curve-Uncoupled		Floor rating		Adapter	6" x 11"	Floors	3" Wood
Braking ratio - Empty	NA	Floor height	3'-8 7/16"	Truck side bearing	NA	Lading anchors	M.F. (40)
Braking ratio - Loaded	NA			Horz. center plate liner	NA		
Braking ratio - H.B.	NA			Vertical wear ring	NA		
				Coupler/Knuckle	Туре Е		
				Yoke	AAR		
				Draft sill/Striker assy.	Fabricated		
				Front draft lug	Fabricated		
				Rear draft lug	Fabricated		
FORMER ROAD NUMBE	RS			Center plate	NA		
CB&Q 94001-94049				Cp. carr. wear plt.	NA		
				Uncoupling rod	NA		
NOTES AND EXCEPTIONS:							
							PAGE F77